

## Camera de supraveghere ip dome

- ..... Megapixel HD IP Vandal Camera with PoE and Audio
- ..... 1/2.8" 1080P low lux CMOS sensor
- ..... ONVIF
- ..... 2.8-12mm Manual Zoom Lens (3M Pixels)
- ..... IR LED:  $\phi$  5X42PCS
- ..... IR range: 40M
- ..... Water resistance: IP66
- ..... DC12V/ 500mA-2000mA/ PoE IEEE 802.3af
- ..... 1ch Audio IN, support microphone, 1ch Audio OUT



Cod Produs PM-20IP40PA

### Specification

System	Camera de supraveghere IP DOME
Image Sensor	1080P low lux CMOS sensor
Size	1/2.8"
Min. scene illumination	0.01lux (0 lux/IR ON)
Infrared sensitivity	Support
IR Filter	IR-CUT
IR-led	42pcs
IR distance	40m
Lens	2.8-12mm 3Mega pixels Vari-focal HD Lens
Compression	H.264 Main Profile
Picture Resolution	1920*1080@30fps
Stream flow	Support dual stream
Bit Rate	128-8192kbps
Bit Rate Type	CBR/VBR
S/N Ratio	>50db
Image enhancement	Auto White Balance, Backlight compensation, Brightness, Contrast, Saturation adjusted
Audio Interface	1ch Audio input optional(Red), support microphone; 1ch Audio output(White)
Audio Compression	G.711
Protocol	HTTP, TCP/IP, UDP, PPPOE, DDNS, DNS, SNTP, DHCP, FTP, RTP, RTSP, UPNP, ONVIF
Ethernet	Ethernet (10/100 Base-T),RJ-45 connector
WEB Browser	Microsoft Internet Explorer 6.0 and above, Google chrome, Firefox, Safari etc.
Safety	IP address filtering, User level password protection. The user acces log
Mobile Phone	IOS/Android
Software Management	CMS and the devices Compatible with ONVIF
Remote Access	DDNS, Software, P2P
Power source	DC12V/ 500-2000mA / PoE protocols IEEE 802.3af
Dimension	$\phi$ 120 x 93(H)mm
Operation temperature	-10~+50 Celsius
Humidity	-10~85%