

## Digital Video Recorder

- ..... 16CH CIF real-time
- ..... Audio in/out: 4CH in/ 1CH out
- ..... Supports Web ,CMS,XMEYE
- ..... Video output: 1CH VGA ,1CH HDMI OUT
- ..... H.264 standard compression
- ..... Two high-speed USB2.0 interfaces
- ..... Support 1 SATA HDD up to 6TB
- ..... DC 12V/4A



Cod Proodus HS-6716CIF

### Specification

System	Digital Video Recorder
Operating System	Embedded LINUX operating system
System resources	Embedded Linux
System resources	Multi-channel real-time recording synchronously multi-channel real-time playback multi-user network operation, USB back up.
Operation interface	16 bit real color GUI interface
Display screen	1/4/8/9/16 screen
DVR mode	16CH real-time
Monitor quality	BNC:D1; VGA:1080P; HDMI:1080P
Encode capability	16CH CIF realtime
Decode capability	1CH*1080P real time
Motion detection	Each channel can be set 192(16*12)detection area Set multi-level of flexibility (for local analog channel only)
Audio compression	G.711A
Audio in/out	4CH RCA /1CH RCA
Alarm in/out	-
Local playback	16 CIF realtime
Video storage	Local HDD, Network
Back up mode	Network backup, USB portable HDD
Video input	16CH BNC
Video output	1CH BNC(960H); 1CH VGA(1080P); 1CH HDMI(1080P)
Network interface	RJ45 10M/100M self-adaptive Ethernet port
USB Interface	2*USB 2.0
Mobile monitoring	Support iPhone, Android and Blackberry etc.
PTZ control	built-in RS485; support multi Protocols
Wireless port	-
Power Supply	12V/4A
Weight	3 KG (without HDD)