

DVR HYBRID 16ch 5 IN 1

- 16CH Hybrid 5 in 1
- 16CH 1080N @15FPS (960*1080P)
- Support Analog/AHD/CVI/TVI and IP Camera
- Supporting all kinds of Cameras
- Support VGA, HDMI HD output
- 2*SATA port, 6TB
- Audio in: 4CH
- DC 12V/4A
- Dimension 335mm*220mm*50mm



Cod Produs RA-16CH1080N

Specification

| System | DVR HYBRID 16ch 5 IN 1 |
|------------------------|---|
| Main processor | Hi 3521A 4G |
| Operating System | Embedded LINUX |
| Video compression | H.264 |
| Mixed Video | AHD: 16CH 1080N@15fps/16CH*1080N@12fps AHD +IP: 12CH 1080N@15fps+4CH*1080P@25fps/8*1080N@15fps+8CH1080P@25fps/4CH 1080N@15fps+12CH 1080P@25fps IP: 16CH 960P@25fps/4*3M@25fps/4CH 5M@25fps |
| Audio | 4CH in/ 1CH out |
| Video output | 1 *HDMI, 1 *VGA, 1 * BNC, Coutputing the images simultaneously |
| Resolution | 16*1080N@15fps /16*960P/4*3M/4*5M) @ 25fps (digital channel) |
| Playback | 16ch 1080N@12fps/4ch 3M@25fps/2CH*5M@25fps, (networking) |
| Scanning System | Progressive Scan |
| Recording /Screenshot | manual record, ATiming record, Amotion detection record, Aalarm record |
| Playback | Instant Playback, ARegular Playback, AEvent Playback, ATag Playback, Alog playback |
| Type HDD | 2* SATA port |
| MUM Capacity | 6TB for each port |
| eSATA | None |
| Alarm Port | Yes |
| PTZ Port | 1 * RS485 |
| Network interface | 1 *RJ45, 10M/100M/1000M |
| USB port | 2 *USB2.0 |
| Networking Protocol | ONVIF, IPv6, AUPnP(plug and play), ANTP(Time-Amendment), ASADP (Search IP address automatically), etc |
| Power Supply | DC 12V/4A |
| Working temperature | -10°C +55°C |
| Working Humidness | 10% - 90% |
| Size | 335mm (L) *220mm (W) *50mm (H) |
| Weight (excluding HDD) | 2.0Kg |