

HD-SDI DIGITAL VIDEO RECORDERS

4 CH HD-SDI DVR

Realtime Video Recording: 4 CH realtime 1080P

Audio In/Out: RCA 4CH in, 1CH ou

Alarm In/Out: Alarm 4CH in, 1CH ou

3G & WIFI (extension via USB port)

2 SATA Hard Disk interface (Up to 6TB)

PTZ, RS485, RS232, P2P, USB, HDMI

DC 12V/ 6A

Dimension : 370*300*60mm



Cod Produs IST-2404SDI

SPECIFICATION

System	Digital Video Recorder
Operating System	Embedded LINUX Operating System
Main Processor	Industrial Grade Embedded Micro Controller Huawei Hisilicon Chipset
System Resources	Multi-channel Real-time Recording Synchronously, Multi-channel Real-time Playback, Multi-channel and Multi-user Network Operation, USB Backup.
Video Input/Output	HD-SDI 4CH input; BNC 2CH output(1CH Spot output), VGA 1CH output, 1 x HDMI (1080P) output
Video Standard	PAL(625 TV Lines, 50fps); NTSC(525TV Lines, 60fps)
Video Image Encode	H.264(Main Profile)
Video Monitor Quality	VGA, HDMI, Full HD 1920*1080
Video Playback Quality	1080P/720P/960H/D1/HD1/CIF/QCIF
Realtime Video Recording	4 CH real time 1080P(1920*1080), PAL: 100 fps, NTSC: at 120 fps
Local Playback	1CH (1*1080P@25fps)
Audio Compression	G.711A
Talkback	Yes
Encode Capability	4 CH Real time 1080P
Decode Capability:	1 CH Real time 1080P
Snapshot	N/A
Plug to Play(P2P)	iCloud Software, Plug to Play(no more need to set the router)
Audio Input/Output	RCA 4CH in, 1CH out
Alarm Input/Output	Alarm 4CH in, 1CH out
Backup Mode	Local Hard Drive Disk, Network
Network Port/PTZ Control	1*RJ45 10/100 Base-T Self-adaptive Ethernet Port/1*RS485, 1*RS232; Support Multi Kinds of PTZ Protocols
HDD Port	2 SATA HDD(Max 6TB)
Wireless Port	3G & WIFI (extension via USB port)
Network Protocols	DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, E-mail, IP Authority, IP Search, Alarm Center
Mobile Surveillance	iPad, iPhone, BlackBerry, Windows, Symbian & Android Mobile Phone
Power Supply	DC12V/6A
Weight	5 KG (without HDD)