

Link catre produs: <https://www.mprotect.ro/camera-supraveghere-ahd-p-34.html>

Camera supraveghere AHD



Pret	79.48 Lei
Disponibilitate	Disponibil
Timpul de livrare	24 ore
Numar de catalog	RA-25A3A

Descrierea produsului

Camera de supraveghere ahd

- Camera AHD
- 2.0 Mega Pixel, IR Cut Filter
- Effective Pixels: 1920*1080P
- 3.6mm Lens
- IR LED: 14 μ ϕ 12PCS
- IR range: 20M
- Water resistance: IP66
- DC12V \pm 10%, 500mA
- Dimension 154x58x62 mm

[RA-25A3A](#)



System	Camera de supraveghere AHD
Image Sensor	1/2.7" SC2235
DSP	FH320
Image Resolution	2.1MP
Mega Pixels	1920*1080P
Video Output Mode	AHD
Usable Illumination	0.001Lux
TV System	PAL/NTSC
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s
Sync System	Internal
S/N Ratio	>50dB
Scanning System	Progressive Scan
Day/Night	Auto / Color / B&W
OSD/UTC Menu Language	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR
White Balance	Auto/ Manual
Gain Control	Auto
Noise Reduction	3D NR
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Infrared LED	14 μ ϕ 24PCS SMT LED
Infrared Distance	20m
Weatherproof Housing	Yes, Metal
IR Cut Filter	Yes
Operation Temperature	-10°C ~ +50°C RH95% Max
Power Source	DC12V \pm 10%, 500mA
Dimension	154x58x62 mm

Descarca specificatiile in format PDF: [RA-25A3A](#)

Camera de supraveghere AHD cu rezolutie 1080P

Effective Pixels: 1920*1080P

3.6mm Lens

IR LED: 14 μ 12PCS

IR range: 20M

Water resistance: IP66

2.0 Mega Pixel, IR Cut Filter

DC12V \pm 10%, 500mA

Dimension 154x58x62 mm

Image Sensor: 1/2.7" SC2235

DSP: FH320

Image Resolution: 1920*1080P

Mega Pixels: 2.1MP

Usable Illumination: 0.001Lux

Video Output Mode: AHD

TV System: PAL/NTSC

Electronic Shutter: 1/25s~1/50,000s , 1/30s~1/60,000s

Sync System: Internal

S/N Ratio:>50dB

Scanning System: Progressive Scan

Day/Night: Auto / Color / B&W



White Balance: Auto/ Manual
Gain Control: Auto
Focus Length: 3.6mm
Focus Control: Fixed
Noise Reduction: 3D NR
Lens Type: Fixed
Infrared LED: 14μ□24PCS SMT LED
Weatherproof Housing: Yes, Metal
Infrared Distance: 20m
IR Cut Filter: Yes
Operation Temperature: -10°C ~ +50°C RH95% Max
Power Source: DC12V±10%, 500mA
Dimension: 154x58x62 mm