

Link catre produs: <https://www.mprotect.ro/dvr-16-canale-5mp-p-9.html>

DVR 16 canale 5MP

Pret	467.00 Lei
Disponibilitate	Disponibil
Timpul de livrare	24 ore
Numar de catalog	MP-1016A

Descrierea produsului

Digital Video Recorder XVR

- 16 canale 5.0MP
- Format H.265/H.264
- AHD TVI CVI CVBS Auto input and IP Camera
- Compatible with all brand of cameras
- 1*SATA port,6TB;
- HDMI,VGA output
- Web viewer, CMS & Mobile, Support P2P Technology
- DC 12V/2A

[MP-1016A](#)



System	Digital Video Recorder AHD
Operating System	Embedded LINUX
Main processor	Hi3521D
Video compression	H.265/H.264
Operation menu	16-bit true color graphical menu interface, mouse operation supported
Resolution	Analog: 8CH 5MP-N/8CH 1080P; Analog+IP camera: 8CH 5MP+8CH 960P IP camera: 4*5MP/8*3MP/16*1080P
Audio input/output	1ch in/ 1ch out
Display	1/16 display (take the pure coaxial input mode as an example)
Output	VGA (1080P), HDMI (4K)
Preview	16*5MN@12fps(AHD/TVI/CVI)/16*4MN@15fps/16*3MN@18fps/16*1080P@25fps/16*720P@25fps
Record	16*5MN@6fps(AHD/TVI/CVI)/16*4MN@8fps/16*3MN@10fps/16*1080P@15fps/16*720P@15fps
Decord	16*5MN@6fps(AHD/TVI/CVI)/16*4MN@8fps/16*3MN@10fps/16*1080P@15fps/16*720P@15fps
NVR	4*5MP/8*3MP/16*1080P
Internal HDD	1 SATA ports, up to 6TB
Recording mode	Manual, Alarm. Motion Detect, Timer
Local playback	8 Channel (when Analog mode)
Video search	Time, Date,Event,Channel search
Network interface	1 *RJ45
USB port	2 ports, USB2.0
Ethernet	RJ-45 port, 10/100M
Backup	Network backup, external HDD, USB Drive, HDD
Remote config	CMS, Mobile Phone Remote Mōnitoring, Support P2P Technology
Power Supply	DC12V/2A ;
Consumption	120W(without HDD)
Working temprature	-10°C- +55°C
Working Humidness	10%--90%
Weight (excluding HDD)	<1.5Kg

Descarca specificatiile in format PDF: [MP-1016A](#)

Digital Video Recorder XVR

16 canale 5.0MP
AHD TVI CVI CVBS Auto input and IP Camera
Compatible with all brand of cameras
1*SATA port,6TB;
HDMI,VGA output
Web viewer, CMS & Mobile, Support P2P Technology
Format H.265/H.264
DC 12V/2A

Analog: 16CH 5MP-N/8CH 1080P;
Analog+IP camera: 8CH 5MP+8CH 960P
IP camera: 4*5MP/8*3MP/16*1080P

DisplayOutput: 1/16 display (take the pure coaxial input mode as an example)
Preview: 16*5MN@12fps(AHD/TVI/CVI)/16*4MN@15fps/16*3MN@18fps/16*1080P@25fps/16*720P@25fps
Record: 16*5MN@6fps(AHD/TVI/CVI)/16*4MN@8fps/16*3MN@10fps/16*1080P@15fps/16*720P@15fps



Decord: 16*5MN@6fps(AHD/TVI/CVI)/16*4MN@8fps/16*3MN@10fps/16*1080P@15fps/16*720P@15fps

Recording mode: Manual, Alarm. Motion Detect, Timer

Local playback: 8 Channel (when Analog mode)

Network interface: 1 x RJ45

USB port: 2 ports, USB2.0

Ethernet: 1 x RJ-45 port, 10/100M

Backup: Network backup, external HDD, USB Drive, HDD

Remote config: CMS, Mobile Phone Remote Monitoring, Support P2P Technoloy