

Link catre produs: <https://www.mprotect.ro/dvr-4-canale-5mp-p-8.html>

DVR 4 canale 5MP



Pret	233.00 Lei
------	-------------------

Disponibilitate	Disponibil
-----------------	-------------------

Timpul de livrare	24 ore
-------------------	---------------

Numar de catalog	MP-1004A-E
------------------	-------------------

Descrierea produsului

Digital Video Recorder XVR

- 4 canale 5.0MP

- Format H.265/H.264

- AHD TVI CVI CVBS Auto input and IP Camera

- Compatible with all brand of cameras

- 1*SATA port,6TB;

- HDMI,VGA output

- Web viewer, CMS & Mobile, Support P2P Technology

- DC 12V/2A



MP-1004A-E



System	Digital Video Recorder AHD
Operating System	Embedded LINUX
Main processor	Hi3520D V400
Video compression	H.265/H.264
Operation menu	16-bit true color graphical menu interface, mouse operation supported
Resolution	Analog: 4CH 5MP-N/4CH 1080P; Analog+IP camera:2CH 5MP-N+2CH 1080P IP camera: 4CH 5MP-N/ 8CH 1080P
Audio input/output	N/A
Display	1/4 display (take the pure coaxial input mode as an example)
Output	VGA (1080P), HDMI (4K)
Preview	4CH*5MN@25fps /4CH*3MN@25fps/4CH*1080p@25fps/4CH*720P@25fps
Record	4CH*5MN@8fps/4CH*3MN@10fps/4CH*1080p@25fps/4CH*720P@25fps
Decord	4CH*5MN/4CH*4MN@8fps/4CH*3MN@10fps/4CH*1080p@25fps/4CH*720P@25fps
NVR	4CH*5MP/8CH*1080P
Internal HDD	1 SATA ports, up to 6TB
Recording mode	Manual, Alarm. Motion Detect, Timer
Local playback	4 Channel (when Analog mode)
Video search	Time, Date,Event,Channel search
Network interface	1 *RJ45
USB port	2 ports, USB2.0
Ethernet	RJ-45 port, 10/100M
Backup	Network backup, external HDD, USB Drive, HDD
Remote config	CMS, Mobile Phone Remote Mbnitoring, Support P2P Technology
Power Supply	DC12V/2A ;
Consuption	120W(without HDD)
Working temprature	-10°C- +55°C
Working Humidness	10%--90%
Weight (excluding HDD)	<1.2Kg

Descarca specificatiile in format PDF: [MP-1004A-E](#)

Digital Video Recorder XVR

4 canale 5.0MP

Format H.265 / H.264

AHD TVI CVI CVBS Auto input and IP Camera

Compatible with all brand of cameras

1 * Port SATA, 6TB;

HDMI, ieşire VGA

Web Viewer, CMS si mobil, suporta P2P Technology

DC 12V / 2A

Analog: 4CH 5MP-N / 1080P

Analog + IP: 2CH 5MP + 2CH 1080P

IP: 4CH 5MP-N / 8CH 1080P

Display: Iesire 1/4

Preview : 4CH * 5MN @ 25fps / 4CH * 3MN @ 25fps / 4CH * 1080p @ 25fps / 4CH * 720P @ 25fp

Record: 4CH * 5MN @ 8fps / 4CH * 3MN @ 10fps / 4CH * 1080p @ 25fps / 4CH * 720P @

Recording mode: Manual, Alarm. Motion Detect, Timer

Port USB: 2 porturi, USB2.0

Ethernet: port RJ-45, 10 / 100M

Backup: Network backup, external HDD, USB Drive, HD



Internal HDD: 1 * Port SATA, 6TB;

Remote config: configCMS, Monitorizare la distanță pentru telefon mobil, Suport Tehnologie P2P