

Link catre produs: <https://www.mprotect.ro/dvr-5in1-cu-16-canale-1080p-p-26.html>

## DVR 5in1 cu 16 canale 1080P



Pret	<b>596.00 Lei</b>
Disponibilitate	<b>Disponibil</b>
Timpul de livrare	<b>24 ore</b>
Numar de catalog	<b>RA-16CH1080P</b>

### Descrierea produsului

#### DVR HYBRID 16ch 5 IN 1

- 16CH Hybrid 5 in 1
- 16CH 1080P @20FPS (1920\*1080P )
- Support Analog/AHD/CVI/TVI and IP Camera
- Supporting all kinds of Cameras
- Support VGA, HDMI HD output
- 2\*SATA port, 6TB
- Audio in: 4CH
- DC 12V/4A
- Dimension 335mm\*220mm\*50mm



Cod Produs RA-16CH1080P

[RA-16CH1080P](#)

System	DVR HYBRID 16ch 5 IN 1
Main processor	Hi 3531A 8G
Operating System	Embedded LINUX
Video compression	H.264
Mixed Video	<b>AHD:</b> 16CH 1080P@12fps/16CH*1080P@20fps/16CH 1080N@25fps/ <b>AHD +IP:</b> 12CH 1080P@15fps+4CH*1080P@25fps/8*1080P@15fps+8CH 1080P@25fps/4CH*1080P@15fps+12CH 1080P@25fps <b>IP:</b> 8CH*3M@25fps/4*4M@25fps
Audio	4CH in/ 1CH out
Video output	1 *HDMI, 1 *VGA, 1 * BNC, Coutputing the images simultaneously
Resolution	16*1080P @ 12fps /16*1080P, 8*3M/4*4M) @ 25fps (digital channel)
Playback	16ch 1080P@12fps /8ch 3M@25fps/4CH*4M@25fps/16ch 1080P@25fps (inetworking)
Scanning System	Progressive Scan
Recording /Screenshot	manual record, ATiming record, Amotion detection record, Aalarm record
Playback	Instant Playback, ARegular Playback, AEvent Playback, ATag Playback, Alog playback
Type HDD	2* SATA port
MUM Capacity	6TB for each port
eSATA	None
Alarm Port	Yes
PTZ Port	1 * RS485
Network interface	1 *RJ45, 10M/100M/1000M
USB port	2 *USB2.0
Networking Protocol	ONVIF, IPv6, AUPnP(plug and play), ANTP(Time-Amendment), ASADP (Search IP address automatically), etc
Power Supply	DC 12V/4A
Working temperature	-10°C +55°C
Working Humidness	10% - 90%
Size	335mm (L) *220mm (W) *50mm (H)
Weight (excluding HDD)	2.0Kg

Descarca specificatiile in format PDF: [RA-16CH1080P](#)

**DVR, cu rezolutie fullHD, DVR 16 video canale, rezolutie 1080P.**

DVR HYBRID 16 canale 5 IN 1  
16CH 1080P @20FPS (1920\*1080P )  
Support Analog/AHD/CVI/TVI and IP Camera  
Supporting all kinds of Cameras Support VGA, HDMI HD output  
2\*SATA port, 6TB  
Audio in: 4CH  
Video compression: H264  
AHD: 16CH 1080P@12fps/16CH\*1080P@20fps/16CH 1080N@25fps/  
AHD+IP: 12CH 1080P@15fps+4CH\*1080P@25fps/8\*1080P@15fps+8CH 1080P@25fps/4CH\*1080P@15fps+12CH 1080P@25fps  
IP: 8CH\*3M@25fps/4\*4M@25fps  
Resolution: 16\*1080P @ 12fps /16\*1080P, 8\*3M/4\*4M) @ 25fps (digital channel)  
Playback: 16ch 1080P@12fps /8ch 3M@25fps/4CH\*4M@25fps/16ch 1080P@25fps  
Recording /Screenshot: manual record, ATiming record, Amotion detection record, Aalarm record  
Type HDD: 2\* SATA port  
MUM Capacity: 6TB for each port  
PTZ port: 1 \* RS485  
Network interface: 1 \*RJ45, 10M/100M/1000M  
USB port: 2 \*USB2.0



**SC MPROTECT CCTV SRL**

Adresa: Bd. Iuliu Maniu, nr. 170-174  
Registrul Comertului: J2014006443402  
CUI: RO 33223750

---

Networking protocol: ONVIF, IPv6, AUPnP(plug and play), ANTP(Time-Amendment), ASADP (Search IP address automatically), etc  
Power Supply: DC 12V/4A (alimentator inclus)  
Temperature: -10°C +55°C  
Size: 335mm (L) \*220mm (W) \*50mm (H)