

Link catre produs: <https://www.mprotect.ro/dvr-8-canale-5mp-p-7.html>

DVR 8 canale 5MP



Pret	336.00 Lei
------	-------------------

Disponibilitate	Disponibil
-----------------	-------------------

Timpul de livrare	24 ore
-------------------	---------------

Numar de catalog	MP-1008A
------------------	-----------------

Descrierea produsului

Digital Video Recorder XVR

- 8 canale 5.0MP
- Format H.265/H.264
- AHD TVI CVI CVBS Auto input and IP Camera
- Compatible with all brand of cameras
- 1*SATA port,6TB;
- HDMI,VGA output
- Web viewer, CMS & Mobile, Support P2P Technology
- DC 12V/2A



DVR 8 canale 5MP



System	Digital Video Recorder AHD
Operating System	Embedded LINUX
Main processor	Hi3520D V400
Video compression	H.265/H.264
Operation menu	16-bit true color graphical menu interface, mouse operation supported
Resolution	Analog: 8CH 5MP-N/8CH 1080P; Analog+IP camera: 4CH 5MP+4CH 960P IP camera: 4*5MP/8*1080P/16*960P
Audio input/output	4ch in/ 1ch out
Display	1/8 display (take the pure coaxial input mode as an example)
Output	VGA (1080P), HDMI (4K)
Preview	8*5MN@12fps/8*4MN@15fps/8*3MN@18fps/8*1080P@25fps/8*720P@25fps
Record	8*5MN@6fps/8*4MN@8fps/8*3MN@10fps/8*1080P@15fps/8*720P@15fps
Decord	8*5MN@6fps/8*4MN@8fps/8*3MN@10fps/8*1080P@15fps/8*720P@15fps
NVR	4*5MP/8*1080P/16*960P
Internal HDD	1 SATA ports, up to 6TB
Recording mode	Manual, Alarm. Motion Detect, Timer
Local playback	8 Channel (when Analog mode)
Video search	Time, Date,Event,Channel search
Network interface	1 *RJ45
USB port	2 ports, USB2.0
Ethernet	RJ-45 port, 10/100M
Backup	Network backup, external HDD, USB Drive, HDD
Remote config	CMS, Mobile Phone Remote Mðnitoring, Support P2P Technology
Power Supply	DC12V/2A ;
Consuption	120W(without HDD)
Working temprature	-10°C- +55°C
Working Humidness	10%--90%
Weight (excluding HDD)	<1.2Kg

Descarca specificatiile in format PDF: [MP-1008A](#)

Digital Video Recorder XVR

8 canale 5.0MP

Format H.265/H.264

AHD TVI CVI CVBS Auto input and IP Camera

Compatible with all brand of cameras

1*SATA port,6TB;

HDMI,VGA output

Web viewer, CMS & Mobile, Support P2P Technology

DC 12V/2A

Analog: 8CH 5MP-N

Analog+IP: 4CH 5MP+4CH 960P

IP: 4CH 5MP/8CH 1080P

Display Output1/8 display

Preview: 8*5MN@12fps/8*4MN@15fps/8*3MN@18fps/8*1080P@25fps/8*720P@25fps

Record: 8*5MN@6fps/8*4MN@8fps/8*3MN@10fps/8*1080P@15fps/8*720P@15fps

Recording mode: Manual, Alarm. Motion Detect, Time

Local playback: 8 Channel (when Analog mod

Network interface: 1 x RJ45

USB port2 ports, USB2.0



Ethernet: RJ-45 port, 10/100M

Backup: Network backup, external HDD, USB Drive, HDD

Remote config: CMS, Mobile Phone Remote Monitoring, Support P2P Technology